



J·DRAIN®

Prefabricated Drainage Composites

DRAINAGE CORE PHYSICAL PROPERTIES

PRODUCTS	WIDTH feet (meters)	THICKNESS (ASTM D 1777) inch (mm)	COMPRESSION (ASTM D 1621) psf (kNm ²)	FLOW (ASTM D 4716) gal/min/ft (L/min/m)
DIMPLE CORE				
Wrap	4, 6.5, 8 (1.22, 1.98, 2.44)	.31 (7.87)	5,200 (249)	12.5 (155)
150/150T	4, 6.5, 8 (1.22, 1.98, 2.44)	.31 (7.87)	5,200 (249)	12.5 (155)
200/220	4, 6.5, 8 (1.22, 1.98, 2.44)	.40 (10.16)	11,000 (527)	18 (223)
400/420	4, 6.5, 8 (1.22, 1.98, 2.44)	.40 (10.16)	15,000 (718)	21 (261)
400/420XL	4, 6.5, 8 (1.22, 1.98, 2.44)	.40 (10.16)	16,500 (790)	21 (261)
500	4 (1.22)	.40 (10.16)	15,000 (718)	21 (261)
700/720	4, 6.5, 8 (1.22, 1.98, 2.44)	.40 (10.16)	21,000 (1005)	23 (286)
780	4, 6.5, 8 (1.22, 1.98, 2.44)	.40 (10.16)	21,000 (1005)	23 (286)
990	4 (1.22)	.40 (10.16)	33,000 (1580)	24 (298)
(Hydraulic Gradient = 1)				
GEONET CORE				
300/302	4, 7 (1.22, 2.13)	.25 (6.35)	40,000 (1915)	8.5 (106)
1000	4 (1.22)	.25 (6.35)	40,000 (1915)	8.5 (106)
(Hydraulic Gradient = 1)				
GREEN ROOF				
GRS	4 (1.22)	1.0 (25.4)	9,500 (455)	30 (372) (HG=.1)
GRS50	4 (1.22)	.40 (10.16)	15,000 (718)	21 (261) (HG=1)
400 RB	4 (1.22)	.40 (10.16)	15,000 (718)	21 (261) (HG=1)
STRIP DRAIN				
SWD	6", 12", 18", 24", 36"	1.0 (25.4)	9,500 (455)	30 (372)

FILTER FABRIC PHYSICAL PROPERTIES

PRODUCTS	APPARENT OPENING SIZE (ASTM D 4751) U.S. STAND. SIEVE (mm)	WATER FLOW RATE (ASTM D 4491) gal/min/ft ² (l/min/m ²)	GRAB TENSILE (ASTM D 4632) lbs. (Kn)	GRAB ELONGATION (ASTM D 4632) %	CBR PUNCTURE (ASTM D 6241) lbs. (Kn)
DIMPLE CORE					
Wrap	N/A	N/A	N/A	N/A	N/A
150 (4ozNW)	70 (0.21)	140 (5704)	100 (0.45)	50	250 (1.11)
150T (grey4ozNW)	70 (0.21)	90 (3657)	120 (0.54)	35	300 (1.32)
200/220 (4ozNW)	70 (0.21)	140 (5704)	100 (0.45)	50	250 (1.11)
400/420 (4ozNW)	70 (0.21)	140 (5704)	100 (0.45)	50	250 (1.11)
400/420XL (6ozNW)	70 (0.21)	110 (4481)	160 (0.71)	50	410 (1.83)
500 (4ozNW)	70 (0.21)	140 (5704)	100 (0.45)	50	250 (1.11)
700/720 (Woven)	40 (0.425)	60 (2460)	370 (1.64)	15	850 (3.78)
780 (8ozNW)	80 (0.18)	95 (3879)	205 (0.90)	50	500 (2.22)
990 (Woven)	40 (0.425)	60 (2460)	370 (1.64)	15	850 (3.78)
GEONET CORE					
300/302 (4ozNW)	70 (0.21)	140 (5704)	100 (0.45)	50	250 (1.11)
1000 (grey6ozNW)	70 (0.21)	110 (4481)	160 (0.71)	50	410 (1.83)
GREEN ROOF					
GRS/GRS50/400RB (RR Fabric)	50 (0.30)	165 (6723)	75 (0.33)	40	160 (0.71)
STRIP DRAIN					
SWD (4ozNW)	70 (0.21)	140 (5704)	100 (0.45)	50	250 (1.11)
MVP (4ozNW)	70 (0.21)	140 (5704)	100 (0.45)	50	250 (1.11)

The information contained herein is believed by JDR Enterprises, Inc. to be accurate and is offered solely for the customer's consideration, investigation and verification. Determination of suitability for use is the responsibility of the user. JDR's Limitations, Limited Warranty, & Disclaimer along with Standard Terms & Conditions apply. See www.j-drain.com for more info. **Limitations:** J-Drain is resistant to chemicals in normal soil environments. However, some reagents may affect the performance of J-Drain. A JDR representative should be contacted for further information to determine the suitability of use of J-Drain in unusual soil environments. J-Drain should be limited to its exposure to ultra-violet sunlight. J-Drain should be backfilled or covered within seven days of installation. **Disclaimer:** All information, drawings and specifications are based on the latest published information at the time of printing. JDR reserves the right to make changes due to manufacturing improvements and engineering at any time. All physical properties are minimum average roll values (MARV). Standard variations of 10% in mechanical properties and 15% in hydraulic properties are normal.

info@j-drain.com

www.j-drain.com

JDR Enterprises, Inc.

292 S. Main St., Suite 200 Alpharetta, GA 30009
(800) 843-7569 (770) 442-1461 Fax: (770) 664-7951